# TECHNICAL SPECIFICATION KENT HANDLE

### 1. Gauge

Caliber	6	7	8	9
Weight ( g ) Packaging	631-720	556-630	489-555	426-488
	10	12	14	
	381-425	320-380	276-320	

## 2. Physical-Chemical Aspects

MODALITY	MARITIME	AERIAL
BRIX	6.5-8	8-10
LOCK %	> 20%	>40%
TEXTURE	Hard	Hard
TOLERANCE	5%	10%
COLOR	dim yellow	dim yellow
SHAPE	Maximum of 10% of fruits with slight formation	Maximum of 10% of fruits with slight formation
WEIGHT	Maximum 10% of fruits out of range with a maximum of +/- 2gr.	Maximum 10% of fruits out of range with a maximum of +/- 2gr.

### 3. Appearance and Quality of Fruit

### Fruit quality in the category

Fresh mangoes of green, reddish/purple color or a mixture of both, of good quality and with the characteristic shape of the variety, firm, healthy and clean. Free of insect bites, mechanical and pathological damage, free of visible foreign matter, may allow slight defects as long as they do not affect the general appearance of the fruit.

#### **TOLERANCE OF FIRST CATEGORY DEFECTS:**

- A 10% second category quality will be considered in the finished product box.

DEFECTS	DEGREE
natural stains	
Insolation	
misshapen	

# TECHNICAL SPECIFICATION KENT HANDLE

damage by want	Mild, in 10% of the surface of the fruit.
Powdery mildew damage	

### **Second Category Fruit Quality**

Fresh mangoes of green, reddish/purple color or a mixture of both, of good quality and with the characteristic shape of the variety, firm, healthy and clean. Free of insect bites, mechanical and pathological damage, free of visible foreign matter, they are You may allow shape defects, scabs, scratches, scars that do not exceed 3 cm2.

### **TOLERANCE OF FIRST CATEGORY DEFECTS:**

- A 20% quality of the National Market will be considered. In a second category box.

DEFECTS	DEGREE
natural stains	
Insolation	
latex stains	
scars	
Red spider	Mild, in 20% of the surface of the fruit.
Thrips	
bed bug damage	
Powdery mildew damage	
Black spots	

**MINOR DEFECTS:** The combination of all defects must not exceed 10% per box.

**MAJOR DEFECTS: The combination of all** *major and minor* defects must not exceed 10% per box.